



PARAMETERS IN ACCORDANCE WITH "ErP" AND "ENERGY LABEL" DIRECTIVES
2009/125/EC AND 2010/30/EU - STANDARD EN 12897

WATER STORAGE TANK MODEL	STANDING LOSS (W)	STANDING LOSS (kWh/24h)	SPECIFIC LOSS (W/K)	STORAGE VOLUME (L)	EFFICIENCY CLASS
INTERACUM. AQUATANK HP 200 LT	67	1,6	1,48	190	C
INTERACUM. AQUATANK HP 300 LT	85	2,03	1,88	263	C
INTERACUM. AQUATANK HP 400 LT	115	2,76	2,55	374	D
INTERACUM. AQUATANK HP 500 LT	130	3,13	2,9	470	D
INTERACUM. AQUATANK HP 800 LT RIGIDO	164	3,93	3,64	702	NOT APPLICABLE
INTERACUM. AQUATANK HP 800 LT BLANDO	174	4,18	3,87	702	NOT APPLICABLE
INTERACUM. AQUATANK HP 1000 LT RIGIDO	180	4,33	4,01	815	NOT APPLICABLE
INTERACUM. AQUATANK HP 1000 LT BLANDO	193	4,63	4,29	815	NOT APPLICABLE