

Technical parameters

Model(s):	Outdoor unit: AQUE-120-V3	Indoor unit: AQU1-160-V3
Air-to-water heat pump:	YES	
Water-to-water heat pump:	NO	
Brine-to-water heat pump:	NO	
Low-temperature heat pump:	NO	
Equipped with a supplementary heater:	YES	
Heat pump combination heater:	NO	
Declared climate condition:	AVERAGE	

Parameters are declared for medium-temperature application.

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	12	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 C	Pdh	10.9	kW
Tj = 2 C	Pdh	7.0	kW
Tj = 7 C	Pdh	4.2	kW
Tj = 12 C	Pdh	2.5	kW
Tj = bivalent temperature	Pdh	10.3	kW
Tj = operating limit	Pdh	10.3	kW
For air-to-water heat pumps: Tj = -15 C	Pdh	-	kW
Bivalent temperature	T _{biv}	-10	°C
Cycling interval capacity for heating	P _{cy} ch	-	kW
Degradation co-efficient (**)	C _{dh}	0.9	--
Power consumption in modes other than active mode			
Off mode	P _{off}	0.019	kW
Standby mode	P _{sb}	0.019	kW
Thermostat-off mode	P _{to}	0.078	kW
Crankcase heater mode	P _{ck}	0.014	kW

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	L _{WA}	45 / 68	dB
Annual energy consumption	Q _{HE}	7835	kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η _s	127	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 C	COP _d	2.02	-
Tj = 2 C	COP _d	3.05	-
Tj = 7 C	COP _d	4.49	-
Tj = 12 C	COP _d	5.97	-
Tj = bivalent temperature	COP _d	1.73	-
Tj = operating limit	COP _d	1.73	-
For air-to-water heat pumps: Tj = -15 C	COP _d	-	-
For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval efficiency	COP _{cy}	-	-
Heating water operating limit temperature	W _{TOL}	60	°C
Supplementary heater			
Rated heat output (**)	P _{sup}	2.0	kW
Type of energy input	Electrical		

For air-to-water heat pumps: Rated air flow rate, outdoors	-	6500	m ³ /h
For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h

For heat pump combination heater:							
Declared load profile	-			Water heating energy efficiency	η _{wh}	-	%
Daily electricity consumption	Q _{elec}	-	kWh	Daily fuel consumption	Q _{fuel}	-	kWh
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ
Contact details	EUROFRED S.A. Cl. Marqués de Sentmenat, 97 - 08029 Barcelona - Spain MADE IN P.R.C						

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

Technical parameters							
Model(s):	Outdoor unit: AQUE-120-V3		Indoor unit: AQU1-160-V3				
Air-to-water heat pump:	YES						
Water-to-water heat pump:	NO						
Brine-to-water heat pump:	NO						
Low-temperature heat pump:	NO						
Equipped with a supplementary heater:	YES						
Heat pump combination heater:	NO						
Declared climate condition:	COLDER						
Parameters are declared for medium-temperature application.							
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	12	kW	Seasonal space heating energy efficiency	η_s	99	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 C	Pdh	7.7	kW	Tj = -7 C	COPd	2.12	-
Tj = 2 C	Pdh	4.6	kW	Tj = 2 C	COPd	2.91	-
Tj = 7 C	Pdh	2.9	kW	Tj = 7 C	COPd	4.08	-
Tj = 12 C	Pdh	2.4	kW	Tj = 12 C	COPd	6.00	-
Tj = bivalent temperature	Pdh	9.9	kW	Tj = bivalent temperature	COPd	1.78	-
Tj = operating limit	Pdh	7.0	kW	Tj = operating limit	COPd	1.28	-
For air-to-water heat pumps: Tj = -15 C	Pdh	-	kW	For air-to-water heat pumps: Tj = -15 C	COPd	-	-
Bivalent temperature	T _{biv}	-15	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-20	°C
Cycling interval capacity for heating	P _{cych}	-	kW	Cycling interval efficiency	COP _{cyc}	-	-
Degradation co-efficient (**)	C _{dh}	0.9	--	Heating water operating limit temperature	W _{TOL}	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{off}	0.019	kW	Rated heat output (**)	P _{sup}	12.1	kW
Standby mode	P _{sb}	0.019	kW	Type of energy input	Electrical		
Thermostat-off mode	P _{to}	0.078	kW				
Crankcase heater mode	P _{ck}	0.014	kW				
Other items							
Capacity control	variable						
Sound power level, indoors/outdoors	L _{WA}	-	dB	For air-to-water heat pumps: Rated air flow rate, outdoors	-	6500	m³/h
Annual energy consumption	Q _{HE}	11694	kWh	For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m³/h
For heat pump combination heater:							
Declared load profile				Water heating energy efficiency			
-				η_{wh}	-		
Daily electricity consumption	Q _{elec}	-	kWh	Daily fuel consumption	Q _{fuel}	-	kWh
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ
Contact details				EUROFRED S.A. Cl. Marqués de Sentmenat, 97 - 08029 Barcelona - Spain MADE IN P.R.C.			
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).							
(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.							

Technical parameters

Model(s):	Outdoor unit: AQUE-120-V3 Indoor unit: AQU1-160-V3
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with a supplementary heater:	YES
Heat pump combination heater:	NO
Declared climate condition:	WARMER

Parameters are declared for medium-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	12	kW	Seasonal space heating energy efficiency	η_s	170	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 C	Pdh	-	kW	Tj = -7 C	COPd	-	-
Tj = 2 C	Pdh	12.0	kW	Tj = 2 C	COPd	2.41	-
Tj = 7 C	Pdh	7.8	kW	Tj = 7 C	COPd	3.52	-
Tj = 12 C	Pdh	5.3	kW	Tj = 12 C	COPd	6.33	-
Tj = bivalent temperature	Pdh	12.0	kW	Tj = bivalent temperature	COPd	2.41	-
Tj = operating limit	Pdh	12.0	kW	Tj = operating limit	COPd	2.41	-
For air-to-water heat pumps: Tj = -15 C	Pdh	-	kW	For air-to-water heat pumps: Tj = -15 C	COPd	-	-
Bivalent temperature	T _{biv}	2	°C	For air-to-water heat pumps: Operation limit temperature	TOL	2	°C
Cycling interval capacity for heating	P _{cych}	-	kW	Cycling interval efficiency	COP _{cyc}	-	-
Degradation co-efficient (**)	C _{dh}	0.9	--	Heating water operating limit temperature	W _{TOL}	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{off}	0.019	kW	Rated heat output (**)	P _{sup}	0	kW
Standby mode	P _{sb}	0.019	kW	Type of energy input	Electrical		
Thermostat-off mode	P _{to}	0.078	kW				
Crankcase heater mode	P _{ck}	0.014	kW				

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	L _{WA}	-	dB
Annual energy consumption	Q _{HE}	3151	kWh
For air-to-water heat pumps: Rated air flow rate, outdoors	-	6500	m ³ /h
For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h

For heat pump combination heater:							
Declared load profile	-			Water heating energy efficiency	η_{wh}	-	%
Daily electricity consumption	Q _{elec}	-	kWh	Daily fuel consumption	Q _{fuel}	-	kWh
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ

Contact details: EUROFRED S.A.
Cl. Marqués de Sentmenat, 97 - 08029 Barcelona - Spain
MADE IN P.R.C

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.