

Technical parameters

Model(s):		Outdoor unit: AOWD-V3-140		Indoor unit: AIWD-V3-160																																																																																																																																																																																																																																	
Air-to-water heat pump:		YES																																																																																																																																																																																																																																			
Water-to-water heat pump:		NO																																																																																																																																																																																																																																			
Brine-to-water heat pump:		NO																																																																																																																																																																																																																																			
Low-temperature heat pump:		NO																																																																																																																																																																																																																																			
Equipped with a supplementary heater:		YES																																																																																																																																																																																																																																			
Heat pump combination heater:		NO																																																																																																																																																																																																																																			
Declared climate condition:		AVERAGE																																																																																																																																																																																																																																			
Parameters are declared for medium-temperature application.																																																																																																																																																																																																																																					
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 25%;">Item</th> <th style="width: 15%;">Symbol</th> <th style="width: 15%;">Value</th> <th style="width: 15%;">Unit</th> <th style="width: 20%;">Item</th> <th style="width: 15%;">Symbol</th> <th style="width: 15%;">Value</th> <th style="width: 15%;">Unit</th> </tr> </thead> <tbody> <tr> <td>Rated heat output (*)</td> <td>Prated</td> <td>14</td> <td>kW</td> <td>Seasonal space heating energy efficiency</td> <td>η_s</td> <td>128</td> <td>%</td> </tr> <tr> <td colspan="4">Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj</td> <td colspan="4">Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj</td> </tr> <tr> <td>Tj = -7 °C</td> <td>Pdh</td> <td>12.2</td> <td>kW</td> <td>Tj = -7 °C</td> <td>COPd</td> <td>2.00</td> <td>-</td> </tr> <tr> <td>Tj = 2 °C</td> <td>Pdh</td> <td>8.3</td> <td>kW</td> <td>Tj = 2 °C</td> <td>COPd</td> <td>3.14</td> <td>-</td> </tr> <tr> <td>Tj = 7 °C</td> <td>Pdh</td> <td>5.0</td> <td>kW</td> <td>Tj = 7 °C</td> <td>COPd</td> <td>4.56</td> <td>-</td> </tr> <tr> <td>Tj = 12 °C</td> <td>Pdh</td> <td>2.7</td> <td>kW</td> <td>Tj = 12 °C</td> <td>COPd</td> <td>6.24</td> <td>-</td> </tr> <tr> <td>Tj = bivalent temperature</td> <td>Pdh</td> <td>12.3</td> <td>kW</td> <td>Tj = bivalent temperature</td> <td>COPd</td> <td>2.00</td> <td>-</td> </tr> <tr> <td>Tj = operating limit temperature</td> <td>Pdh</td> <td>10.3</td> <td>kW</td> <td>Tj = operating limit temperature</td> <td>COPd</td> <td>1.66</td> <td>-</td> </tr> <tr> <td>For air-to-water heat pumps: Tj = -15 °C</td> <td>Pdh</td> <td>-</td> <td>kW</td> <td>For air-to-water heat pumps: Tj = -15 °C</td> <td>COPd</td> <td>-</td> <td>-</td> </tr> <tr> <td>Bivalent temperature</td> <td>T_{biv}</td> <td>-7</td> <td>°C</td> <td>For air-to-water heat pumps: Operation limit temperature</td> <td>TOL</td> <td>-10</td> <td>°C</td> </tr> <tr> <td>Cycling interval capacity for heating</td> <td>P_{cych}</td> <td>-</td> <td>kW</td> <td>Cycling interval efficiency</td> <td>COP_{cyt}</td> <td>-</td> <td>-</td> </tr> <tr> <td>Degradation co-efficient (**)</td> <td>C_{dh}</td> <td>0.9</td> <td>--</td> <td>Heating water operating limit temperature</td> <td>W_{TOL}</td> <td>60</td> <td>°C</td> </tr> <tr> <td colspan="4">Power consumption in modes other than active mode</td> <td colspan="4">Supplementary heater</td> </tr> <tr> <td>Off mode</td> <td>P_{off}</td> <td>0.019</td> <td>kW</td> <td>Rated heat output (**)</td> <td>P_{sup}</td> <td>3.5</td> <td>kW</td> </tr> <tr> <td>Standby mode</td> <td>P_{sb}</td> <td>0.019</td> <td>kW</td> <td>Type of energy input</td> <td colspan="3">Electrical</td> </tr> <tr> <td>Thermostat-off mode</td> <td>P_{to}</td> <td>0.078</td> <td>kW</td> <td colspan="4"></td> </tr> <tr> <td>Crankcase heater mode</td> <td>P_{ck}</td> <td>0.014</td> <td>kW</td> <td colspan="4"></td> </tr> <tr> <td colspan="4">Other items</td> <td colspan="4"></td> </tr> <tr> <td>Capacity control</td> <td colspan="3">variable</td> <td>For air-to-water heat pumps: Rated air flow rate, outdoors</td> <td>-</td> <td>6500</td> <td>m³/h</td> </tr> <tr> <td>Sound power level, indoors/ outdoors</td> <td>L_{WA}</td> <td>45 / 71</td> <td>dB</td> <td>For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger</td> <td>-</td> <td>-</td> <td>m³/h</td> </tr> <tr> <td>Annual energy consumption</td> <td>Q_{HE}</td> <td>8692</td> <td>kWh</td> <td colspan="4"></td> </tr> <tr> <td colspan="8">For heat pump combination heater:</td> </tr> <tr> <td colspan="2">Declared load profile</td> <td colspan="2">-</td> <td colspan="2">Water heating energy efficiency</td> <td>η_{wh}</td> <td>-</td> </tr> <tr> <td>Daily electricity consumption</td> <td>Q_{elec}</td> <td>-</td> <td>kWh</td> <td>Daily fuel consumption</td> <td>Q_{fuel}</td> <td>-</td> <td>kWh</td> </tr> <tr> <td>Annual electricity consumption</td> <td>AEC</td> <td>-</td> <td>kWh</td> <td>Annual fuel consumption</td> <td>AFC</td> <td>-</td> <td>GJ</td> </tr> <tr> <td colspan="2">Contact details</td> <td colspan="6">EUROFRED S.A. Cl. Marqués de Sentmenat, 97 - 08029 Barcelona - Spain MADE IN P.R.C</td> </tr> <tr> <td colspan="8"> (*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9. </td> </tr> </tbody> </table>						Item	Symbol	Value	Unit	Item	Symbol	Value	Unit	Rated heat output (*)	Prated	14	kW	Seasonal space heating energy efficiency	η_s	128	%	Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj				Tj = -7 °C	Pdh	12.2	kW	Tj = -7 °C	COPd	2.00	-	Tj = 2 °C	Pdh	8.3	kW	Tj = 2 °C	COPd	3.14	-	Tj = 7 °C	Pdh	5.0	kW	Tj = 7 °C	COPd	4.56	-	Tj = 12 °C	Pdh	2.7	kW	Tj = 12 °C	COPd	6.24	-	Tj = bivalent temperature	Pdh	12.3	kW	Tj = bivalent temperature	COPd	2.00	-	Tj = operating limit temperature	Pdh	10.3	kW	Tj = operating limit temperature	COPd	1.66	-	For air-to-water heat pumps: Tj = -15 °C	Pdh	-	kW	For air-to-water heat pumps: Tj = -15 °C	COPd	-	-	Bivalent temperature	T _{biv}	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C	Cycling interval capacity for heating	P _{cych}	-	kW	Cycling interval efficiency	COP _{cyt}	-	-	Degradation co-efficient (**)	C _{dh}	0.9	--	Heating water operating limit temperature	W _{TOL}	60	°C	Power consumption in modes other than active mode				Supplementary heater				Off mode	P _{off}	0.019	kW	Rated heat output (**)	P _{sup}	3.5	kW	Standby mode	P _{sb}	0.019	kW	Type of energy input	Electrical			Thermostat-off mode	P _{to}	0.078	kW					Crankcase heater mode	P _{ck}	0.014	kW					Other items								Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	6500	m ³ /h	Sound power level, indoors/ outdoors	L _{WA}	45 / 71	dB	For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h	Annual energy consumption	Q _{HE}	8692	kWh					For heat pump combination heater:								Declared load profile		-		Water heating energy efficiency		η_{wh}	-	Daily electricity consumption	Q _{elec}	-	kWh	Daily fuel consumption	Q _{fuel}	-	kWh	Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ	Contact details		EUROFRED S.A. Cl. Marqués de Sentmenat, 97 - 08029 Barcelona - Spain MADE IN P.R.C						(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.							
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit																																																																																																																																																																																																																														
Rated heat output (*)	Prated	14	kW	Seasonal space heating energy efficiency	η_s	128	%																																																																																																																																																																																																																														
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj																																																																																																																																																																																																																																	
Tj = -7 °C	Pdh	12.2	kW	Tj = -7 °C	COPd	2.00	-																																																																																																																																																																																																																														
Tj = 2 °C	Pdh	8.3	kW	Tj = 2 °C	COPd	3.14	-																																																																																																																																																																																																																														
Tj = 7 °C	Pdh	5.0	kW	Tj = 7 °C	COPd	4.56	-																																																																																																																																																																																																																														
Tj = 12 °C	Pdh	2.7	kW	Tj = 12 °C	COPd	6.24	-																																																																																																																																																																																																																														
Tj = bivalent temperature	Pdh	12.3	kW	Tj = bivalent temperature	COPd	2.00	-																																																																																																																																																																																																																														
Tj = operating limit temperature	Pdh	10.3	kW	Tj = operating limit temperature	COPd	1.66	-																																																																																																																																																																																																																														
For air-to-water heat pumps: Tj = -15 °C	Pdh	-	kW	For air-to-water heat pumps: Tj = -15 °C	COPd	-	-																																																																																																																																																																																																																														
Bivalent temperature	T _{biv}	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C																																																																																																																																																																																																																														
Cycling interval capacity for heating	P _{cych}	-	kW	Cycling interval efficiency	COP _{cyt}	-	-																																																																																																																																																																																																																														
Degradation co-efficient (**)	C _{dh}	0.9	--	Heating water operating limit temperature	W _{TOL}	60	°C																																																																																																																																																																																																																														
Power consumption in modes other than active mode				Supplementary heater																																																																																																																																																																																																																																	
Off mode	P _{off}	0.019	kW	Rated heat output (**)	P _{sup}	3.5	kW																																																																																																																																																																																																																														
Standby mode	P _{sb}	0.019	kW	Type of energy input	Electrical																																																																																																																																																																																																																																
Thermostat-off mode	P _{to}	0.078	kW																																																																																																																																																																																																																																		
Crankcase heater mode	P _{ck}	0.014	kW																																																																																																																																																																																																																																		
Other items																																																																																																																																																																																																																																					
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	6500	m ³ /h																																																																																																																																																																																																																														
Sound power level, indoors/ outdoors	L _{WA}	45 / 71	dB	For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h																																																																																																																																																																																																																														
Annual energy consumption	Q _{HE}	8692	kWh																																																																																																																																																																																																																																		
For heat pump combination heater:																																																																																																																																																																																																																																					
Declared load profile		-		Water heating energy efficiency		η_{wh}	-																																																																																																																																																																																																																														
Daily electricity consumption	Q _{elec}	-	kWh	Daily fuel consumption	Q _{fuel}	-	kWh																																																																																																																																																																																																																														
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ																																																																																																																																																																																																																														
Contact details		EUROFRED S.A. Cl. Marqués de Sentmenat, 97 - 08029 Barcelona - Spain MADE IN P.R.C																																																																																																																																																																																																																																			
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj). (**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.																																																																																																																																																																																																																																					

Technical parameters

Model(s):	Outdoor unit: AOWD-V3-140	Indoor unit: AIWD-V3-160
Air-to-water heat pump:	YES	
Water-to-water heat pump:	NO	
Brine-to-water heat pump:	NO	
Low-temperature heat pump:	NO	
Equipped with a supplementary heater:	YES	
Heat pump combination heater:	NO	
Declared climate condition:	COLDER	

Parameters are declared for medium-temperature application.

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	14	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 C	Pdh	8.8	kW
Tj = 2 C	Pdh	5.3	kW
Tj = 7 C	Pdh	3.3	kW
Tj = 12 C	Pdh	2.4	kW
Tj = bivalent temperature	Pdh	10.5	kW
Tj = operating limit temperature	Pdh	7.1	kW
For air-to-water heat pumps: Tj = -15 C	Pdh	-	kW
Bivalent temperature	Tbiv	-12	°C
Cycling interval capacity for heating	Pcych	-	kW
Degradation co-efficient (**)	Cdh	0.9	--
Power consumption in modes other than active mode			
Off mode	Poff	0.019	kW
Standby mode	Psb	0.019	kW
Thermostat-off mode	Pto	0.078	kW
Crankcase heater mode	Pck	0.014	kW

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	LWA	-	dB
Annual energy consumption	QHE	13314	kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	ηs	103	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 C	COPd	2.19	-
Tj = 2 C	COPd	3.17	-
Tj = 7 C	COPd	4.40	-
Tj = 12 C	COPd	6.15	-
Tj = bivalent temperature	COPd	1.85	-
Tj = operating limit temperature	COPd	1.29	-
For air-to-water heat pumps: Tj = -15 C	COPd	-	-
For air-to-water heat pumps: Operation limit temperature	TOL	-20	°C
Cycling interval efficiency	COP _{cy}	-	-
Heating water operating limit temperature	WTOL	60	°C
Supplementary heater			
Rated heat output (**)	Psup	14.3	kW
Type of energy input	Electrical		

For air-to-water heat pumps: Rated air flow rate, outdoors	-	6500	m ³ /h
For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h

For heat pump combination heater:							
Declared load profile	-			Water heating energy efficiency	η _{wh}	-	%
Daily electricity consumption	Q _{elec}	-	kWh	Daily fuel consumption	Q _{fuel}	-	kWh
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ

Contact details	EUROFRED S.A. Cl. Marqués de Sentmenat, 97 - 08029 Barcelona - Spain MADE IN P.R.C						
-----------------	--	--	--	--	--	--	--

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

Technical parameters

Model(s):	Outdoor unit: AOWD-V3-140 Indoor unit: AIWD-V3-160
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with a supplementary heater:	YES
Heat pump combination heater:	NO
Declared climate condition:	WARMER

Parameters are declared for medium-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	14	kW	Seasonal space heating energy efficiency	η_s	165	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 C	Pdh	-	kW	Tj = -7 C	COPd	-	-
Tj = 2 C	Pdh	14.0	kW	Tj = 2 C	COPd	2.31	-
Tj = 7 C	Pdh	9.3	kW	Tj = 7 C	COPd	3.45	-
Tj = 12 C	Pdh	4.2	kW	Tj = 12 C	COPd	5.76	-
Tj = bivalent temperature	Pdh	14.0	kW	Tj = bivalent temperature	COPd	2.31	-
Tj = operating limit	Pdh	14.0	kW	Tj = operating limit	COPd	2.31	-
For air-to-water heat pumps: Tj = -15 C	Pdh	-	kW	For air-to-water heat pumps: Tj = -15 C	COPd	-	-
Bivalent temperature	T _{biv}	2	°C	For air-to-water heat pumps: Operation limit temperature	TOL	2	°C
Cycling interval capacity for heating	P _{cych}	-	kW	Cycling interval efficiency	COP _{cyc}	-	-
Degradation co-efficient (**)	C _{dh}	0.9	-	Heating water operating limit temperature	W _{TOL}	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P _{off}	0.019	kW	Rated heat output (**)	P _{sup}	0	kW
Standby mode	P _{sb}	0.019	kW	Type of energy input	Electrical		
Thermostat-off mode	P _{to}	0.078	kW				
Crankcase heater mode	P _{ck}	0.014	kW				

Other items							
Capacity control	variable						
Sound power level, indoors/ outdoors	L _{WA}	-	dB	For air-to-water heat pumps: Rated air flow rate, outdoors	-	6500	m ³ /h
Annual energy consumption	Q _{HE}	3780	kWh	For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h

For heat pump combination heater:

Declared load profile	-			Water heating energy efficiency	η_{wh}	-	%
Daily electricity consumption	Q _{elec}	-	kWh	Daily fuel consumption	Q _{fuel}	-	kWh
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ

Contact details
EUROFRED S.A.
Cl. Marqués de Sentmenat, 97 - 08029 Barcelona - Spain
MADE IN P.R.C

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.