

### Technical parameters

Model(s):	Outdoor unit: AOWD-V3-160    Indoor unit: AIWD-V3-160
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with a supplementary heater:	YES
Heat pump combination heater:	NO
Declared climate condition:	AVERAGE

Parameters are declared for medium-temperature application.

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	15	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	11.5	kW
Tj = 2 °C	Pdh	8.1	kW
Tj = 7 °C	Pdh	5.2	kW
Tj = 12 °C	Pdh	2.5	kW
Tj = bivalent temperature	Pdh	12.0	kW
Tj = operating limit	Pdh	10.3	kW
For air-to-water heat pumps: Tj = -15 °C	Pdh	-	kW
Bivalent temperature	T <sub>biv</sub>	-5	°C
Cycling interval capacity for heating	P <sub>cy</sub> ch	-	kW
Degradation co-efficient (**)	C <sub>dh</sub>	0.9	--
Power consumption in modes other than active mode			
Off mode	P <sub>off</sub>	0.019	kW
Standby mode	P <sub>sb</sub>	0.019	kW
Thermostat-off mode	P <sub>to</sub>	0.078	kW
Crankcase heater mode	P <sub>ck</sub>	0.014	kW

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	L <sub>WA</sub>	45 / 72	dB
Annual energy consumption	Q <sub>HE</sub>	9697	kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η <sub>s</sub>	124	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	COP <sub>d</sub>	1.95	-
Tj = 2 °C	COP <sub>d</sub>	3.05	-
Tj = 7 °C	COP <sub>d</sub>	4.52	-
Tj = 12 °C	COP <sub>d</sub>	5.96	-
Tj = bivalent temperature	COP <sub>d</sub>	2.05	-
Tj = operating limit	COP <sub>d</sub>	1.70	-
For air-to-water heat pumps: Tj = -15 °C	COP <sub>d</sub>	-	-
For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval efficiency	COP <sub>cy</sub>	-	-
Heating water operating limit temperature	W <sub>TOL</sub>	60	°C
Supplementary heater			
Rated heat output (**)	P <sub>sup</sub>	4.6	kW
Type of energy input	Electrical		

For air-to-water heat pumps: Rated air flow rate, outdoors	-	6500	m <sup>3</sup> /h
For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m <sup>3</sup> /h

For heat pump combination heater:							
<b>Declared load profile</b>	-			<b>Water heating energy efficiency</b>	η <sub>wh</sub>	-	%
Daily electricity consumption	Q <sub>elec</sub>	-	kWh	Daily fuel consumption	Q <sub>fuel</sub>	-	kWh
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ

Contact details	EUROFRED S.A. Cl. Marqués de Sentmenat, 97 - 08029 Barcelona - Spain MADE IN P.R.C						
-----------------	--	--	--	--	--	--	--

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

### Technical parameters

Model(s):		Outdoor unit: AOWD-V3-160		Indoor unit: AIWD-V3-160																																																																																																																																																																																																																									
Air-to-water heat pump:		YES																																																																																																																																																																																																																											
Water-to-water heat pump:		NO																																																																																																																																																																																																																											
Brine-to-water heat pump:		NO																																																																																																																																																																																																																											
Low-temperature heat pump:		NO																																																																																																																																																																																																																											
Equipped with a supplementary heater:		YES																																																																																																																																																																																																																											
Heat pump combination heater:		NO																																																																																																																																																																																																																											
Declared climate condition:		COLDER																																																																																																																																																																																																																											
Parameters are declared for medium-temperature application.																																																																																																																																																																																																																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 25%;">Item</th> <th style="width: 10%;">Symbol</th> <th style="width: 15%;">Value</th> <th style="width: 10%;">Unit</th> <th style="width: 25%;">Item</th> <th style="width: 10%;">Symbol</th> <th style="width: 15%;">Value</th> <th style="width: 10%;">Unit</th> </tr> </thead> <tbody> <tr> <td>Rated heat output (*)</td> <td>Prated</td> <td>15</td> <td>kW</td> <td>Seasonal space heating energy efficiency</td> <td><math>\eta_s</math></td> <td>98</td> <td>%</td> </tr> <tr> <td colspan="4">Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj</td> <td colspan="4">Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj</td> </tr> <tr> <td>Tj = -7 °C</td> <td>Pdh</td> <td>8.8</td> <td>kW</td> <td>Tj = -7 °C</td> <td>COPd</td> <td>2.19</td> <td>-</td> </tr> <tr> <td>Tj = 2 °C</td> <td>Pdh</td> <td>5.3</td> <td>kW</td> <td>Tj = 2 °C</td> <td>COPd</td> <td>3.17</td> <td>-</td> </tr> <tr> <td>Tj = 7 °C</td> <td>Pdh</td> <td>3.3</td> <td>kW</td> <td>Tj = 7 °C</td> <td>COPd</td> <td>4.40</td> <td>-</td> </tr> <tr> <td>Tj = 12 °C</td> <td>Pdh</td> <td>2.4</td> <td>kW</td> <td>Tj = 12 °C</td> <td>COPd</td> <td>6.15</td> <td>-</td> </tr> <tr> <td>Tj = bivalent temperature</td> <td>Pdh</td> <td>10.1</td> <td>kW</td> <td>Tj = bivalent temperature</td> <td>COPd</td> <td>1.85</td> <td>-</td> </tr> <tr> <td>Tj = operating limit</td> <td>Pdh</td> <td>7.1</td> <td>kW</td> <td>Tj = operating limit</td> <td>COPd</td> <td>1.29</td> <td>-</td> </tr> <tr> <td>For air-to-water heat pumps: Tj = -15 °C</td> <td>Pdh</td> <td>-</td> <td>kW</td> <td>For air-to-water heat pumps: Tj = -15 °C</td> <td>COPd</td> <td>-</td> <td>-</td> </tr> <tr> <td>Bivalent temperature</td> <td>T<sub>biv</sub></td> <td>-10</td> <td>°C</td> <td>For air-to-water heat pumps: Operation limit temperature</td> <td>TOL</td> <td>-20</td> <td>°C</td> </tr> <tr> <td>Cycling interval capacity for heating</td> <td>P<sub>cych</sub></td> <td>-</td> <td>kW</td> <td>Cycling interval efficiency</td> <td>COP<sub>cyt</sub></td> <td>-</td> <td>-</td> </tr> <tr> <td>Degradation co-efficient (**)</td> <td>C<sub>dh</sub></td> <td>0.9</td> <td>--</td> <td>Heating water operating limit temperature</td> <td>W<sub>TOL</sub></td> <td>60</td> <td>°C</td> </tr> <tr> <td colspan="4">Power consumption in modes other than active mode</td> <td colspan="4">Supplementary heater</td> </tr> <tr> <td>Off mode</td> <td>P<sub>off</sub></td> <td>0.019</td> <td>kW</td> <td>Rated heat output (**)</td> <td>P<sub>sup</sub></td> <td>14.8</td> <td>kW</td> </tr> <tr> <td>Standby mode</td> <td>P<sub>sb</sub></td> <td>0.019</td> <td>kW</td> <td>Type of energy input</td> <td colspan="3">Electrical</td> </tr> <tr> <td>Thermostat-off mode</td> <td>P<sub>to</sub></td> <td>0.078</td> <td>kW</td> <td colspan="4"></td> </tr> <tr> <td>Crankcase heater mode</td> <td>P<sub>ck</sub></td> <td>0.014</td> <td>kW</td> <td colspan="4"></td> </tr> <tr> <td colspan="4">Other items</td> <td colspan="4"></td> </tr> <tr> <td>Capacity control</td> <td colspan="3">variable</td> <td>For air-to-water heat pumps: Rated air flow rate, outdoors</td> <td>-</td> <td>6500</td> <td>m<sup>3</sup>/h</td> </tr> <tr> <td>Sound power level, indoors/ outdoors</td> <td>L<sub>WA</sub></td> <td>-</td> <td>dB</td> <td>For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger</td> <td>-</td> <td>-</td> <td>m<sup>3</sup>/h</td> </tr> <tr> <td>Annual energy consumption</td> <td>Q<sub>HE</sub></td> <td>14451</td> <td>kWh</td> <td colspan="4"></td> </tr> <tr> <td colspan="8">For heat pump combination heater:</td> </tr> <tr> <td>Declared load profile</td> <td colspan="3">-</td> <td>Water heating energy efficiency</td> <td><math>\eta_{wh}</math></td> <td>-</td> <td>%</td> </tr> <tr> <td>Daily electricity consumption</td> <td>Q<sub>elec</sub></td> <td>-</td> <td>kWh</td> <td>Daily fuel consumption</td> <td>Q<sub>fuel</sub></td> <td>-</td> <td>kWh</td> </tr> <tr> <td>Annual electricity consumption</td> <td>AEC</td> <td>-</td> <td>kWh</td> <td>Annual fuel consumption</td> <td>AFC</td> <td>-</td> <td>GJ</td> </tr> <tr> <td>Contact details</td> <td colspan="7">EUROFRED S.A. Cl. Marqués de Sentmenat, 97 - 08029 Barcelona - Spain MADE IN P.R.C</td> </tr> </tbody> </table>						Item	Symbol	Value	Unit	Item	Symbol	Value	Unit	Rated heat output (*)	Prated	15	kW	Seasonal space heating energy efficiency	$\eta_s$	98	%	Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj				Tj = -7 °C	Pdh	8.8	kW	Tj = -7 °C	COPd	2.19	-	Tj = 2 °C	Pdh	5.3	kW	Tj = 2 °C	COPd	3.17	-	Tj = 7 °C	Pdh	3.3	kW	Tj = 7 °C	COPd	4.40	-	Tj = 12 °C	Pdh	2.4	kW	Tj = 12 °C	COPd	6.15	-	Tj = bivalent temperature	Pdh	10.1	kW	Tj = bivalent temperature	COPd	1.85	-	Tj = operating limit	Pdh	7.1	kW	Tj = operating limit	COPd	1.29	-	For air-to-water heat pumps: Tj = -15 °C	Pdh	-	kW	For air-to-water heat pumps: Tj = -15 °C	COPd	-	-	Bivalent temperature	T <sub>biv</sub>	-10	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-20	°C	Cycling interval capacity for heating	P <sub>cych</sub>	-	kW	Cycling interval efficiency	COP <sub>cyt</sub>	-	-	Degradation co-efficient (**)	C <sub>dh</sub>	0.9	--	Heating water operating limit temperature	W <sub>TOL</sub>	60	°C	Power consumption in modes other than active mode				Supplementary heater				Off mode	P <sub>off</sub>	0.019	kW	Rated heat output (**)	P <sub>sup</sub>	14.8	kW	Standby mode	P <sub>sb</sub>	0.019	kW	Type of energy input	Electrical			Thermostat-off mode	P <sub>to</sub>	0.078	kW					Crankcase heater mode	P <sub>ck</sub>	0.014	kW					Other items								Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	6500	m <sup>3</sup> /h	Sound power level, indoors/ outdoors	L <sub>WA</sub>	-	dB	For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m <sup>3</sup> /h	Annual energy consumption	Q <sub>HE</sub>	14451	kWh					For heat pump combination heater:								Declared load profile	-			Water heating energy efficiency	$\eta_{wh}$	-	%	Daily electricity consumption	Q <sub>elec</sub>	-	kWh	Daily fuel consumption	Q <sub>fuel</sub>	-	kWh	Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ	Contact details	EUROFRED S.A. Cl. Marqués de Sentmenat, 97 - 08029 Barcelona - Spain MADE IN P.R.C						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit																																																																																																																																																																																																																						
Rated heat output (*)	Prated	15	kW	Seasonal space heating energy efficiency	$\eta_s$	98	%																																																																																																																																																																																																																						
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj																																																																																																																																																																																																																									
Tj = -7 °C	Pdh	8.8	kW	Tj = -7 °C	COPd	2.19	-																																																																																																																																																																																																																						
Tj = 2 °C	Pdh	5.3	kW	Tj = 2 °C	COPd	3.17	-																																																																																																																																																																																																																						
Tj = 7 °C	Pdh	3.3	kW	Tj = 7 °C	COPd	4.40	-																																																																																																																																																																																																																						
Tj = 12 °C	Pdh	2.4	kW	Tj = 12 °C	COPd	6.15	-																																																																																																																																																																																																																						
Tj = bivalent temperature	Pdh	10.1	kW	Tj = bivalent temperature	COPd	1.85	-																																																																																																																																																																																																																						
Tj = operating limit	Pdh	7.1	kW	Tj = operating limit	COPd	1.29	-																																																																																																																																																																																																																						
For air-to-water heat pumps: Tj = -15 °C	Pdh	-	kW	For air-to-water heat pumps: Tj = -15 °C	COPd	-	-																																																																																																																																																																																																																						
Bivalent temperature	T <sub>biv</sub>	-10	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-20	°C																																																																																																																																																																																																																						
Cycling interval capacity for heating	P <sub>cych</sub>	-	kW	Cycling interval efficiency	COP <sub>cyt</sub>	-	-																																																																																																																																																																																																																						
Degradation co-efficient (**)	C <sub>dh</sub>	0.9	--	Heating water operating limit temperature	W <sub>TOL</sub>	60	°C																																																																																																																																																																																																																						
Power consumption in modes other than active mode				Supplementary heater																																																																																																																																																																																																																									
Off mode	P <sub>off</sub>	0.019	kW	Rated heat output (**)	P <sub>sup</sub>	14.8	kW																																																																																																																																																																																																																						
Standby mode	P <sub>sb</sub>	0.019	kW	Type of energy input	Electrical																																																																																																																																																																																																																								
Thermostat-off mode	P <sub>to</sub>	0.078	kW																																																																																																																																																																																																																										
Crankcase heater mode	P <sub>ck</sub>	0.014	kW																																																																																																																																																																																																																										
Other items																																																																																																																																																																																																																													
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	6500	m <sup>3</sup> /h																																																																																																																																																																																																																						
Sound power level, indoors/ outdoors	L <sub>WA</sub>	-	dB	For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m <sup>3</sup> /h																																																																																																																																																																																																																						
Annual energy consumption	Q <sub>HE</sub>	14451	kWh																																																																																																																																																																																																																										
For heat pump combination heater:																																																																																																																																																																																																																													
Declared load profile	-			Water heating energy efficiency	$\eta_{wh}$	-	%																																																																																																																																																																																																																						
Daily electricity consumption	Q <sub>elec</sub>	-	kWh	Daily fuel consumption	Q <sub>fuel</sub>	-	kWh																																																																																																																																																																																																																						
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ																																																																																																																																																																																																																						
Contact details	EUROFRED S.A. Cl. Marqués de Sentmenat, 97 - 08029 Barcelona - Spain MADE IN P.R.C																																																																																																																																																																																																																												
<p>(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).</p> <p>(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.</p>																																																																																																																																																																																																																													

### Technical parameters

Model(s):	Outdoor unit: AOWD-V3-160	Indoor unit: AIWD-V3-160
Air-to-water heat pump:	YES	
Water-to-water heat pump:	NO	
Brine-to-water heat pump:	NO	
Low-temperature heat pump:	NO	
Equipped with a supplementary heater:	YES	
Heat pump combination heater:	NO	
Declared climate condition:	WARMER	

Parameters are declared for medium-temperature application.

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	15	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 C	Pdh	-	kW
Tj = 2 C	Pdh	15.3	kW
Tj = 7 C	Pdh	9.9	kW
Tj = 12 C	Pdh	4.4	kW
Tj = bivalent temperature	Pdh	15.3	kW
Tj = operating limit	Pdh	15.3	kW
For air-to-water heat pumps: Tj = -15 C	Pdh	-	kW
Bivalent temperature	Tbiv	2	°C
Cycling interval capacity for heating	Pcych	-	kW
Degradation co-efficient (**)	Cdh	0.9	--
Power consumption in modes other than active mode			
Off mode	Poff	0.019	kW
Standby mode	Psb	0.019	kW
Thermostat-off mode	Pto	0.078	kW
Crankcase heater mode	Pck	0.014	kW

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	LWA	-	dB
Annual energy consumption	QHE	3839	kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	ηs	178	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 C	COPd	-	-
Tj = 2 C	COPd	2.42	-
Tj = 7 C	COPd	3.80	-
Tj = 12 C	COPd	6.08	-
Tj = bivalent temperature	COPd	2.42	-
Tj = operating limit	COPd	2.42	-
For air-to-water heat pumps: Tj = -15 C	COPd	-	-
For air-to-water heat pumps: Operation limit temperature	TOL	2	°C
Cycling interval efficiency	COP <sub>cy</sub>	-	-
Heating water operating limit temperature	WTOL	60	°C
Supplementary heater			
Rated heat output (**)	Psup	0	kW
Type of energy input	Electrical		

For air-to-water heat pumps: Rated air flow rate, outdoors	-	6500	m <sup>3</sup> /h
For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m <sup>3</sup> /h

For heat pump combination heater:							
Declared load profile	-			Water heating energy efficiency	η <sub>wh</sub>	-	%
Daily electricity consumption	Q <sub>elec</sub>	-	kWh	Daily fuel consumption	Q <sub>fuel</sub>	-	kWh
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ

Contact details: EUROFRED S.A.  
Cl. Marqués de Sentmenat, 97 - 08029 Barcelona - Spain  
MADE IN P.R.C

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).

(\*\*) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.