

REFRIGERANT

R32



# MINICHILLER INVERTER

Series

**MINICHILLER INVERTER CRAD 3 KiAWP**

Edition

**06/22**

Models

**CRAD 3 KiAWP 15**

**CRAD 3 KiAWP 25**

**CRAD 3 KiAWP 35**

**CRAD 3 KiAWP 50**

**CRAD 3 KiAWP 55**

**CRAD 3 KiAWP 60**

**CRAD 3 KiAWP 50T**

**CRAD 3 KiAWP 55T**

**CRAD 3 KiAWP 60T**



# Temperature application

Model	For medium - temperature application												
	Energy efficiency class	Unit sound power	average climate			colder climate			warmer climate				
			Rated heat output	Seasonal space heating energy efficiency	For space heating annual energy consumption	Rated heat output	Seasonal space heating energy efficiency	For space heating annual energy consumption	Rated heat output	Seasonal space heating energy efficiency	For space heating annual energy consumption		
	dB	kW	%	kWh	kW	%	kWh	kW	%	kWh	kW	%	kWh
CRAD3 15 KIAWP	A++	60	6.4	140.7	3655	113.1	4428	6.2	170.9	1895	6.2	170.9	1895
CRAD3 25 KIAWP	A++	63	7.3	143.6	4088	117.7	4948	8.1	185.3	2303	8.1	185.3	2303
CRAD3 35 KIAWP	A++	65	8.2	145.5	4539	122.4	5665	9.0	193.4	2458	9.0	193.4	2458
CRAD3 50 KIAWP	A++	70	12.5	141.6	7148	126.0	8628	12.0	179.0	3524	12.0	179.0	3524
CRAD3 50T KIAWP	A++	70	12.5	141.6	7148	126.0	8628	12.0	179.0	3523	12.0	179.0	3523
CRAD3 55 KIAWP	A++	72	14.2	141.8	8079	126.6	9496	14.2	184.6	4040	14.2	184.6	4040
CRAD3 55T KIAWP	A++	72	14.2	141.8	8079	126.6	9496	14.2	184.7	4039	14.2	184.7	4039
CRAD3 60 KIAWP	A++	72	14.7	140.6	8471	124.3	10473	14.5	184.0	4154	14.5	184.0	4154
CRAD3 60T KIAWP	A++	72	14.7	140.7	8470	124.3	10473	14.5	184.0	4153	14.5	184.0	4153

Model	For low - temperature application												
	Energy efficiency class	Unit sound power	average climate			colder climate			warmer climate				
			Rated heat output	Seasonal space heating energy efficiency	For space heating annual energy consumption	Rated heat output	Seasonal space heating energy efficiency	For space heating annual energy consumption	Rated heat output	Seasonal space heating energy efficiency	For space heating annual energy consumption		
	dB	kW	%	kWh	kW	%	kWh	kW	%	kWh	kW	%	kWh
CRAD3 15 KIAWP	A+++	60	6.5	201.8	2631	173.4	3425	6.2	268.2	1229	6.2	268.2	1229
CRAD3 25 KIAWP	A+++	63	7.9	204.0	3155	174.6	4166	8.1	274.7	1551	8.1	274.7	1551
CRAD3 35 KIAWP	A+++	65	9.1	201.9	3654	174.6	4591	9.0	279.1	1714	9.0	279.1	1714
CRAD3 50 KIAWP	A+++	70	12.3	200.1	5004	168.8	7153	12.1	262.3	2437	12.1	262.3	2437
CRAD3 50T KIAWP	A+++	70	12.3	200.2	5003	168.8	7153	12.1	262.5	2435	12.1	262.5	2435
CRAD3 55 KIAWP	A+++	72	14.2	192.5	5984	171.3	8095	13.2	260.5	2684	13.2	260.5	2684
CRAD3 55T KIAWP	A+++	72	14.2	192.5	5984	171.3	8095	13.2	260.6	2683	13.2	260.6	2683
CRAD3 60 KIAWP	A+++	72	15.2	190.5	6510	170.9	8546	14.2	255.3	2937	14.2	255.3	2937
CRAD3 60T KIAWP	A+++	72	15.2	190.5	6509	170.9	8546	14.2	255.5	2935	14.2	255.5	2935

# Product fiche 1

<b>Mini Inverter heat pump space heating</b>									
	Outdoor	CRAD3 15 KiAWP	CRAD3 25 KiAWP	CRAD3 35 KiAWP	CRAD3 50 KiAWP	CRAD3 55 KiAWP			
Outdoor unit sound power (*)	dB	60	63	65	70	72			
Space heating	dB	60	63	65	70	72			
Space heating	-	A+++	A+++	A+++	A+++	A+++			
Average climate (Design temperature = -10°C)	-	A++	A++	A++	A++	A++			
<b>Space heating 35°C</b>									
Prated (declared heating capacity) @ -10°C	[kW]	6.5	7.9	9.1	12.3	14.2			
Seasonal space heating efficiency (ηs)	[%]	201.8	204.0	201.9	200.1	192.5			
Annual energy consumption	[kWh]	2,631	3,155	3,654	5,004	5,984			
<b>Space heating 55°C</b>									
Prated (declared heating capacity) @ -10°C	[kW]	6.4	7.3	8.2	12.5	14.2			
Seasonal space heating efficiency (ηs)	[%]	140.7	143.6	145.5	141.6	141.8			
Annual energy consumption	[kWh]	3,655	4,088	4,539	7,148	8,079			
<b>Part load conditions space heating average climate low temperature application</b>									
<b>(A) condition (-7°C)</b>									
Pdh (declared heating capacity)	[kW]	5.77	6.99	8.02	10.85	12.52			
COPd (declared COP)	-	3.43	3.29	3.09	3.11	2.97			
Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90			
<b>(B) condition (2°C)</b>									
Pdh (declared heating capacity)	[kW]	3.74	4.51	5.06	6.79	7.98			
COPd (declared COP)	-	5.04	4.99	4.92	4.86	4.56			
Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90			
<b>(C) condition (7°C)</b>									
Pdh (declared heating capacity)	[kW]	2.32	2.81	3.22	4.79	5.04			
COPd (declared COP)	-	6.06	6.72	7.03	6.98	7.01			
Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90			
<b>(D) condition (12°C)</b>									
Pdh (declared heating capacity)	[kW]	1.87	1.87	1.87	3.73	3.73			
COPd (declared COP)	-	9.12	9.12	9.12	9.02	9.02			
Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90			
<b>(E) Tol (temperature operating limit)</b>									
Tol (temperature operating limit)	[°C]	-10.00	-10.00	-10.00	-10.00	-10.00			
Pdh (declared heating capacity)	[kW]	6.52	7.46	7.88	12.30	13.41			
COPd (declared COP)	-	3.00	2.87	2.87	2.80	2.66			
WTOL (Heating water Operation Limit)	[°C]	65	65	65	65	65			

# Product fiche 1

<b>Mini Inverter heat pump space heating</b>						
	Average climate low temperature application	Outdoor	CRAD3 60 KiAWP	CRAD3 50T KiAWP	CRAD3 55T KiAWP	CRAD3 60T KiAWP
Outdoor unit sound power (*)	dB		72	70	72	72
Space heating	Average climate medium temperature application	dB	72	70	72	72
Space heating	Energy efficiency class 35°C (Low temp. app.)	-	A+++	A+++	A+++	A+++
Space heating	Energy efficiency class 55°C (Medium temp. app.)	-	A++	A+	A+	A+
Average climate (Design temperature = -10°C)						
Space heating 35°C	Prated (declared heating capacity) @ -10°C	[kW]	15.2	12.3	14.2	15.2
	Seasonal space heating efficiency (ηs)	[%]	190.5	200.2	192.5	190.5
Space heating 55°C	Annual energy consumption	[kWh]	6,510	5,003	5,984	6,509
	Prated (declared heating capacity) @ -10°C	[kW]	14.7	12.5	14.2	14.7
	Seasonal space heating efficiency (ηs)	[%]	140.6	141.6	141.8	140.7
	Annual energy consumption	[kWh]	8,471	7,148	8,079	8,470
Part load conditions space heating average climate low temperature application						
(A) condition (-7°C)	Pdh (declared heating capacity)	[kW]	13.49	10.85	12.52	13.49
	COPd (declared COP)	-	2.87	3.11	2.97	2.87
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	8.59	6.79	7.98	8.59
	COPd (declared COP)	-	4.53	4.86	4.56	4.53
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	5.55	4.79	5.04	5.55
	COPd (declared COP)	-	7.01	6.98	7.01	7.01
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	3.73	3.73	3.73	3.73
	COPd (declared COP)	-	9.02	9.02	9.02	9.02
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(E) Tol (temperature operating limit)	Tol (temperature operating limit)	[°C]	-10.00	-10.00	-10.00	-10.00
	Pdh (declared heating capacity)	[kW]	14.05	12.30	13.41	14.05
	COPd (declared COP)	-	2.65	2.80	2.66	2.65
	WTOL (Heating water Operation Limit)	[°C]	65	65	65	65

## Product fiche 2

<b>Mini Inverter heat pump space heating</b>									
	Tbiv	Outdoor	CRAD3 15 KiAWP	CRAD3 25 KiAWP	CRAD3 35 KiAWP	CRAD3 50 KiAWP	CRAD3 55 KiAWP		
(F) Tivalent temperature	[°C]	[kW]	-7.00	-7.00	-7.00	-7.00	-7.00	-7.00	-7.00
			5.77	6.99	8.02	10.85	12.52		
			3.43	3.29	3.09	3.11	2.97		
Supplementary capacity at P <sub>design</sub>	[kW]		0.00	0.44	1.18	0.00	0.75		
Part load conditions space heating average climate medium temperature application									
(A) condition (-7°C)	[kW]		5.62	6.42	7.21	11.06	12.52		
			2.36	2.31	2.24	2.15	2.20		
			0.90	0.90	0.90	0.90	0.90		
(B) condition (2°C)	[kW]		3.52	4.03	4.56	6.91	7.71		
			3.70	3.76	3.86	3.59	3.58		
			0.90	0.90	0.90	0.90	0.90		
(C) condition (7°C)	[kW]		2.20	2.56	2.84	4.64	5.07		
			4.21	4.48	4.58	5.07	5.06		
			0.90	0.90	0.90	0.90	0.90		
(D) condition (12°C)	[kW]		1.31	1.31	1.31	2.15	2.15		
			4.96	4.96	4.96	4.52	4.52		
			0.90	0.90	0.90	0.90	0.90		
(E) Tol (temperature operating limit)	[°C]		-10.00	-10.00	-10.00	-10.00	-10.00		
			6.04	6.85	7.01	10.97	11.51		
			2.02	1.98	1.97	1.98	1.96		
WTOL (Heating water Operation Limit)	[°C]		65	65	65	65	65		
Tbiv	[°C]		-7.00	-7.00	-7.00	-7.00	-7.00		
Pdh (declared heating capacity)	[kW]		5.62	6.42	7.21	11.06	12.52		
COPd (declared COP)			2.36	2.31	2.24	2.15	2.20		
Supplementary capacity at P <sub>design</sub>	[kW]		0.32	0.40	1.14	1.53	2.65		
Colder climate (Design temperature = -22°C)									
Prated (declared heating capacity) @ -22°C	[kW]		6.1	7.5	8.3	12.5	14.3		
Seasonal space heating efficiency (ηs)	[%]		173.4	174.6	174.6	168.8	171.3		
Annual energy consumption	[kWh]		3,425	4,166	4,591	7,153	8,095		

## Product fiche 2

<b>Mini Inverter heat pump space heating</b>		Outdoor	CRAD3 60 KiAWP	CRAD3 50T KiAWP	CRAD3 55T KiAWP	CRAD3 60T KiAWP
(F) Tivalent temperature	Tbiv	[°C]	-7.00	-7.00	-7.00	-7.00
	Pdh (declared heating capacity)	[kW]	13.49	10.85	12.52	13.49
	COPd (declared COP)	-	2.87	3.11	2.97	2.87
Supplementary capacity at P <sub>design</sub>	Psup (@Tdesignh: -10°C)	[kW]	1.18	0.00	0.75	1.18
Part load conditions space heating average climate medium temperature application						
(A) condition (-7°C)	Pdh (declared heating capacity)	[kW]	13.03	11.06	12.52	13.03
	COPd (declared COP)	-	2.16	2.15	2.20	2.16
	Cdh (degradation coefficient)	-	0.90	0.90	0.90	0.90
	Pdh (declared heating capacity)	[kW]	8.50	6.91	7.71	8.50
(B) condition (2°C)	COPd (declared COP)	-	3.55	3.59	3.58	3.55
	Cdh (degradation coefficient)	-	0.90	0.90	0.90	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	5.27	4.64	5.07	5.27
	COPd (declared COP)	-	5.05	5.07	5.06	5.05
	Cdh (degradation coefficient)	-	0.90	0.90	0.90	0.90
	Pdh (declared heating capacity)	[kW]	2.15	2.15	2.15	2.15
(D) condition (12°C)	COPd (declared COP)	-	4.52	4.52	4.52	4.52
	Cdh (degradation coefficient)	-	0.90	0.90	0.90	0.90
	Tol (temperature operating limit)	[°C]	-10.00	-10.00	-10.00	-10.00
	Pdh (declared heating capacity)	[kW]	12.07	10.97	11.51	12.07
(E) To (temperature operating limit)	COPd (declared COP)	-	1.94	1.98	1.96	1.94
	WTOL (Heating water Operation Limit)	[°C]	65	65	65	65
	Tbiv	[°C]	-7.00	-7.00	-7.00	-7.00
(F) Tivalent temperature	Pdh (declared heating capacity)	[kW]	13.03	11.06	12.52	13.03
	COPd (declared COP)	-	2.16	2.15	2.20	2.16
	Psup (@Tdesignh: -10°C)	[kW]	2.63	1.53	2.65	2.63
Colder climate (Design temperature = -22°C)						
Space heating 35°C	Prated (declared heating capacity) @ -22°C	[kW]	15.1	12.5	14.3	15.1
	Seasonal space heating efficiency (ηs)	[%]	170.9	168.8	171.3	170.9
	Annual energy consumption	[kWh]	8,546	7,153	8,095	8,546

## Product fiche 3

<b>Mini Inverter heat pump space heating</b>									
	Outdoor	CRAD3 15 KiAWP	CRAD3 25 KiAWP	CRAD3 35 KiAWP	CRAD3 50 KiAWP	CRAD3 55 KiAWP			
Space heating 55°C	Prated (declared heating capacity) @ -22°C	[kW]	5.2	6.1	7.2	11.3	12.5		
	Seasonal space heating efficiency (ηs)	[%]	113.1	117.7	122.4	126.0	126.6		
	Annual energy consumption	[kWh]	4,428	4,948	5,665	8,628	9,496		
Part load conditions space heating colder climate low temperature application									
(A) condition (-7°C)	Pdh (declared heating capacity)	[kW]	4.11	4.42	5.42	8.08	8.74		
	COPd (declared COP)	-	3.76	3.67	3.72	3.64	3.59		
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90		
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	2.38	2.99	3.14	4.93	5.52		
	COPd (declared COP)	-	5.33	5.50	5.56	5.34	5.35		
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90		
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	1.66	2.03	2.16	3.17	3.70		
	COPd (declared COP)	-	5.78	6.69	6.55	5.28	7.06		
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90		
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	1.87	1.87	1.87	3.69	3.69		
	COPd (declared COP)	-	9.12	9.12	9.12	9.34	9.34		
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90		
(E) Tol (temperature operating limit)	Tol (temperature operating limit)	[°C]	-22.00	-22.00	-22.00	-22.00	-22.00		
	Pdh (declared heating capacity)	[kW]	4.21	4.78	5.08	8.72	9.14		
	COPd (declared COP)	-	2.12	2.16	2.01	2.08	2.02		
(F) Tivalent temperature	WTOL (Heating water Operation Limit)	[°C]	65	65	65	65	65		
	Tbiv	[°C]	-15.00	-15.00	-15.00	-15.00	-15.00		
	Pdh (declared heating capacity)	[kW]	5.00	6.12	6.75	10.17	11.67		
Supplementary capacity at P_design	COPd (declared COP)	-	3.02	2.70	2.59	2.66	2.58		
	Psup (@Tdesignh: -22°C)	[kW]	1.92	2.72	3.19	3.78	5.17		
Part load conditions space heating colder climate medium temperature application									
(A) condition (-7°C)	Pdh (declared heating capacity)	[kW]	3.21	3.95	4.59	7.09	7.80		
	COPd (declared COP)	-	2.60	2.75	2.72	2.75	2.77		
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90		



## Product fiche 3

<b>Mini Inverter heat pump space heating</b>						
	Outdoor	CRAD3 60 KIAWP	CRAD3 50T KIAWP	CRAD3 55T KIAWP	CRAD3 60T KIAWP	
Space heating 55°C	[kW]	13.5	11.3	12.5	13.5	
Seasonal space heating efficiency (ηs)	[%]	124.3	126.0	126.6	124.3	
Annual energy consumption	[kWh]	10,473	8,628	9,496	10,473	
<b>Part load conditions space heating colder climate low temperature application</b>						
(A) condition (-7°C)	[kW]	9.26	8.08	8.74	9.26	
	-	3.59	3.64	3.59	3.59	
	-	0.90	0.90	0.90	0.90	
(B) condition (2°C)	[kW]	5.76	4.93	5.52	5.76	
	-	5.35	5.34	5.35	5.35	
	-	0.90	0.90	0.90	0.90	
(C) condition (7°C)	[kW]	3.76	3.17	3.70	3.76	
	-	7.04	5.28	7.06	7.04	
	-	0.90	0.90	0.90	0.90	
(D) condition (12°C)	[kW]	3.72	3.69	3.69	3.72	
	-	8.78	9.34	9.34	8.78	
	-	0.90	0.90	0.90	0.90	
(E) Toi (temperature operating limit)	[°C]	-22.00	-22.00	-22.00	-22.00	
	[kW]	9.43	8.72	9.14	9.43	
	-	2.00	2.08	2.02	2.00	
	[°C]	65	65	65	65	
(F) Tbivalent temperature	[°C]	-15.00	-15.00	-15.00	-15.00	
	[kW]	12.30	10.17	11.67	12.30	
	-	2.58	2.66	2.58	2.58	
Supplementary capacity at P_design	[kW]	5.67	3.78	5.17	5.67	
<b>Part load conditions space heating colder climate medium temperature application</b>						
(A) condition (-7°C)	[kW]	8.43	7.09	7.80	8.43	
	-	2.77	2.75	2.77	2.77	
	-	0.90	0.90	0.90	0.90	

# Product fiche 4

<b>Mini Inverter heat pump space heating</b>		Outdoor	CRAD3 15 KIAWP	CRAD3 25 KIAWP	CRAD3 35 KIAWP	CRAD3 50 KIAWP	CRAD3 55 KIAWP
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	2.03	2.25	2.82	4.44	4.64
	COPd (declared COP)	-	3.18	3.30	3.60	3.88	3.91
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	1.56	1.56	1.76	3.00	3.00
	COPd (declared COP)	-	4.50	4.50	4.84	4.88	4.88
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	1.44	1.44	1.44	3.60	3.61
	COPd (declared COP)	-	5.83	5.83	5.83	6.61	6.61
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90
(E) Tol (temperature operating limit)	Tol (temperature operating limit)	[°C]	-22.00	-22.00	-22.00	-22.00	-22.00
	Pdh (declared heating capacity)	[kW]	3.24	3.24	3.24	7.00	7.28
	COPd (declared COP)	-	1.32	1.32	1.32	1.38	1.35
(F) Tbivalent temperature	WTOL (Heating water Operation Limit)	[°C]	65	65	65	65	65
	Tbiv	[°C]	-15.00	-15.00	-15.00	-15.00	-15.00
	Pdh (declared heating capacity)	[kW]	4.25	4.94	5.88	9.21	10.19
Supplementary capacity at P_design	Ps up (@Tdesign: -22°C)	[kW]	2.00	2.08	2.10	1.92	1.91
<b>Warmer climate (Design temperature = 2°C)</b>							
Space heating 35°C	Prated (declared heating capacity) @ 2°C	[kW]	6.2	8.1	9.0	12.1	13.2
	Seasonal space heating efficiency (ηs)	[%]	268.2	274.7	279.1	262.3	260.5
	Annual energy consumption	[kWh]	1,229	1,551	1,714	2,437	2,684
Space heating 55°C	Prated (declared heating capacity) @ 2°C	[kW]	6.2	8.1	9.0	12.0	14.2
	Seasonal space heating efficiency (ηs)	[%]	170.9	185.3	193.4	179.0	184.6
	Annual energy consumption	[kWh]	1,895	2,303	2,458	3,524	4,040
<b>Part load conditions space heating warmer climate low temperature application</b>							
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	5.69	7.23	8.29	12.10	12.94
	COPd (declared COP)	-	4.31	4.04	3.85	3.53	3.51
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	4.01	5.18	5.81	7.78	8.51
	COPd (declared COP)	-	6.39	6.35	6.24	5.82	5.72
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90

# Product fiche 4

<b>Mini Inverter heat pump space heating</b>		Outdoor	CRAD3 60 KIAWP	CRAD3 50T KIAWP	CRAD3 55T KIAWP	CRAD3 60T KIAWP
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	5.20	4.44	4.64	5.20
	COPd (declared COP)	-	3.74	3.88	3.91	3.74
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	3.53	3.00	3.00	3.53
	COPd (declared COP)	-	5.19	4.88	4.88	5.19
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	3.61	3.60	3.61	3.61
	COPd (declared COP)	-	6.61	6.61	6.61	6.61
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(E) Tol (temperature operating limit)	Tol (temperature operating limit)	[°C]	-22.00	-22.00	-22.00	-22.00
	Pdh (declared heating capacity)	[kW]	7.52	7.00	7.28	7.52
	COPd (declared COP)	-	1.30	1.38	1.35	1.30
(F) Tivalent temperature	WTOL (Heating water Operation Limit)	[°C]	65	65	65	65
	Tbiv	[°C]	-15.00	-15.00	-15.00	-15.00
	Pdh (declared heating capacity)	[kW]	11.03	9.21	10.19	11.03
Supplementary capacity at P_design	COPd (declared COP)	-	1.85	1.92	1.91	1.85
Warmer climate (Design temperature = 2°C)	Psup (@Tdesignh: -22°C)	[kW]	6.00	4.30	5.21	6.00
Space heating 35°C	Prated (declared heating capacity) @ 2°C	[kW]	14.2	12.1	13.2	14.2
	Seasonal space heating efficiency (ηs)	[%]	255.3	262.5	260.6	255.5
	Annual energy consumption	[kWh]	2,937	2,435	2,683	2,935
	Prated (declared heating capacity) @ 2°C	[kW]	14.5	12.0	14.2	14.5
	Seasonal space heating efficiency (ηs)	[%]	184.0	179.0	184.7	184.0
Part load conditions space heating warmer climate low temperature application	Annual energy consumption	[kWh]	4,154	3,523	4,039	4,153
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	14.20	12.10	12.94	14.20
	COPd (declared COP)	-	3.22	3.53	3.51	3.22
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	9.15	7.78	8.51	9.15
	COPd (declared COP)	-	5.41	5.82	5.72	5.41
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90

## Product fiche 5

<b>Mini Inverter heat pump space heating</b>										
	Outdoor	CRAD3 15 KIAWP	CRAD3 25 KIAWP	CRAD3 35 KIAWP	CRAD3 50 KIAWP	CRAD3 55 KIAWP				
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	2.07	2.46	2.67	3.64	3.96			
	COPd (declared COP)	-	8.71	9.30	9.63	8.31	8.51			
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90			
	Tol (temperature operating limit)	[°C]	2.00	2.00	2.00	2.00	2.00			
(E) Tol (temperature operating limit)	Pdh (declared heating capacity)	[kW]	5.69	7.23	8.29	12.10	12.94			
	COPd (declared COP)	-	4.31	4.04	3.85	3.53	3.51			
	WTOL (Heating water Operation Limit)	[°C]	65	65	65	65	65			
	Tbiv	[°C]	7.00	7.00	7.00	7.00	7.00			
(F) Tivalent temperature	Pdh (declared heating capacity)	[kW]	4.01	5.18	5.81	7.78	8.51			
	COPd (declared COP)	-	6.39	6.35	6.24	5.82	5.72			
	Psup (@Tdesignh: 2°C)	[kW]	0.55	0.84	0.75	0.00	0.26			
	Supplementary capacity at P_design									
Part load conditions space heating warmer climate medium temperature application										
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	6.17	7.80	8.42	12.00	13.01			
	COPd (declared COP)	-	2.77	2.68	2.68	2.39	2.37			
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90			
	Pdh (declared heating capacity)	[kW]	3.97	5.22	5.81	7.73	9.12			
(C) condition (7°C)	COPd (declared COP)	-	3.90	4.07	4.16	3.86	3.95			
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90			
	Pdh (declared heating capacity)	[kW]	2.06	2.36	2.74	3.59	4.26			
	COPd (declared COP)	-	5.28	6.07	6.64	5.88	6.37			
(D) condition (12°C)	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90			
	Tol (temperature operating limit)	[°C]	2.00	2.00	2.00	2.00	2.00			
	Pdh (declared heating capacity)	[kW]	6.17	7.80	8.42	12.00	13.01			
	COPd (declared COP)	-	2.77	2.68	2.68	2.39	2.37			
(E) Tol (temperature operating limit)	WTOL (Heating water Operation Limit)	[°C]	65	65	65	65	65			
	Tbiv	[°C]	7.00	7.00	7.00	7.00	7.00			
	Pdh (declared heating capacity)	[kW]	3.97	5.22	5.81	7.73	9.12			
	COPd (declared COP)	-	3.90	4.07	4.16	3.86	3.95			
(F) Tivalent temperature	Psup (@Tdesignh: 2°C)	[kW]	0.00	0.32	0.61	0.00	1.18			
	Supplementary capacity at P_design									

## Product fiche 5

<b>Mini Inverter heat pump space heating</b>		Outdoor	CRAD3 60 KIAWP	CRAD3 50T KIAWP	CRAD3 55T KIAWP	CRAD3 60T KIAWP
(D) condition (12°C)	Pdh (declared heating capacity)	[KW]	4.24	3.64	3.96	4.24
	COPd (declared COP)	-	8.56	8.31	8.51	8.56
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(E) Tol (temperature operating limit)	Tol (temperature operating limit)	[°C]	2.00	2.00	2.00	2.00
	Pdh (declared heating capacity)	[KW]	14.20	12.10	12.94	14.20
	COPd (declared COP)	-	3.22	3.53	3.51	3.22
	WTOL (Heating water Operation Limit)	[°C]	65	65	65	65
	Tbiv	[°C]	7.00	7.00	7.00	7.00
(F) Tivalent temperature	Pdh (declared heating capacity)	[KW]	9.15	7.78	8.51	9.15
Supplementary capacity at P_design	COPd (declared COP)	-	5.41	5.82	5.72	5.41
	Psup (@Tdesignh: 2°C)	[KW]	0.00	0.00	0.26	0.00
<b>Part load conditions space heating warmer climate medium temperature application</b>						
(B) condition (2°C)	Pdh (declared heating capacity)	[KW]	13.62	12.00	13.01	13.62
	COPd (declared COP)	-	2.35	2.39	2.37	2.35
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[KW]	9.35	7.73	9.12	9.35
	COPd (declared COP)	-	3.94	3.86	3.95	3.94
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(D) condition (12°C)	Pdh (declared heating capacity)	[KW]	4.26	3.59	4.26	4.26
	COPd (declared COP)	-	6.37	5.88	6.37	6.37
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(E) Tol (temperature operating limit)	Tol (temperature operating limit)	[°C]	2.00	2.00	2.00	2.00
	Pdh (declared heating capacity)	[KW]	13.62	12.00	13.01	13.62
	COPd (declared COP)	-	2.35	2.39	2.37	2.35
	WTOL (Heating water Operation Limit)	[°C]	65	65	65	65
	Tbiv	[°C]	7.00	7.00	7.00	7.00
(F) Tivalent temperature	Pdh (declared heating capacity)	[KW]	9.35	7.73	9.12	9.35
Supplementary capacity at P_design	COPd (declared COP)	-	3.94	3.86	3.95	3.94
	Psup (@Tdesignh: 2°C)	[KW]	0.91	0.00	1.18	0.91

## Product fiche 6

<b>Mini Inverter heat pump space heating</b>		Outdoor	CRAD3 15 KIAWP	CRAD3 25 KIAWP	CRAD3 35 KIAWP	CRAD3 50 KIAWP	CRAD3 55 KIAWP
Product description	Air-to-water heat pump	Y/N	Yes	Yes	Yes	Yes	Yes
	Water-to-water heat pump	Y/N	No	No	No	No	No
	Brine-to-water heat pump	Y/N	No	No	No	No	No
	Low-temperature heat pump	Y/N	No	No	No	No	No
	Equipped with a supplementary heater	Y/N	Yes	Yes	Yes	Yes	Yes
	Heat pump combination heater	Y/N	Yes	Yes	Yes	Yes	Yes
	Rated airflow (outdoor)	[m <sup>3</sup> /h]	3900	4500	4500	5200	5200
	Rated water/brine flow (outdoor H/E)	-	/	/	/	/	/
Other	Capacity control	-	Inverter	Inverter	Inverter	Inverter	Inverter
	P <sub>off</sub> (Power consumption Off mode)	[kW]	0.013	0.013	0.013	0.013	0.013
	P <sub>to</sub> (Power consumption Thermostat off mode)	[kW]	0.020	0.020	0.020	0.020	0.020
	P <sub>sb</sub> (Power consumption Standby mode)	[kW]	0.013	0.013	0.013	0.013	0.013
	P <sub>ck</sub> (Power crankcase heater model)	[kW]	0.000	0.000	0.000	0.000	0.000
	Q <sub>elec</sub> (Daily electricity consumption)	[kWh]	/	/	/	/	/
	Q <sub>fuel</sub> (Daily fuel consumption)	[kWh]	/	/	/	/	/

Note :

Product fiche data according to energy label directive 2010/30/EC regulation (EU) 811/2013.  
 Sound power measured according to the EN12102 under conditions of the EN14825.  
 Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

## Product fiche 6

### Mini Inverter heat pump space heating

	Outdoor	CRAD3 60 KIAWP	CRAD3 50T KIAWP	CRAD3 55T KIAWP	CRAD3 60T KIAWP
Air-to-water heat pump	Y/N	Yes	Yes	Yes	Yes
Water-to-water heat pump	Y/N	No	No	No	No
Brine-to-water heat pump	Y/N	No	No	No	No
Low-temperature heat pump	Y/N	No	No	No	No
Equipped with a supplementary heater	Y/N	Yes	Yes	Yes	Yes
Heat pump combination heater	Y/N	Yes	Yes	Yes	Yes
Air to water unit	[m <sup>3</sup> /h]	5200	5200	5200	5200
Brine/water to water unit	-	/	/	/	/
Capacity control	-	Inverter	Inverter	Inverter	Inverter
P <sub>off</sub> (Power consumption Off mode)	[kW]	0.013	0.006	0.006	0.006
P <sub>to</sub> (Power consumption Thermostat off mode)	[kW]	0.020	0.018	0.018	0.018
P <sub>sb</sub> (Power consumption Standby mode)	[kW]	0.013	0.006	0.006	0.006
P <sub>ck</sub> (Power crankcase heater model)	[kW]	0.000	0.000	0.000	0.000
Q <sub>elec</sub> (Daily electricity consumption)	[kWh]	/	/	/	/
Q <sub>fuel</sub> (Daily fuel consumption)	[kWh]	/	/	/	/

Note :

a) represents the hydraulic module series ;

b) represents the m-thermal tank series ;

Product fiche data according to energy label directive 2010/30/EC regulation (EU) 811/2013.

Sound power measured according to the EN12102 under conditions of the EN14825.

Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

## Product fiche 7

<b>Mini Inverter heat pump space cooling</b>									
	Outdoor	CRAD3 15 KiAWP	CRAD3 25 KiAWP	CRAD3 35 KiAWP	CRAD3 50 KiAWP	CRAD3 55 KiAWP			
Outdoor unit sound power (*)	dB	62	64	66	69	71			
Average climate low temperature application	dB	62	64	66	69	71			
Average climate medium temperature application	[kW]	5.6	7.4	9.0	11.7	13.5			
Prated (declared cooling capacity) @ 35°C	[%]	200.43	204.71	200.21	199.92	200.65			
Seasonal space cooling efficiency (ηs)	[kWh]	658	854	1,063	1,380	1,592			
Annual energy consumption	[kW]	6.9	8.6	10.2	12.1	14.0			
Prated (declared cooling capacity) @ 35°C	[%]	309.5	320.48	329.48	308.53	300.52			
Seasonal space cooling efficiency (ηs)	[kWh]	527	635	739	932	1,109			
Annual energy consumption	Part load conditions space cooling : low temperature application@7°C								
Pdc (declared cooling capacity)	[kW]	5.58	7.39	9.00	11.67	13.51			
EERd (declared EER)	-	3.38	3.28	2.92	3.11	3.01			
Cdc(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90			
Pdc (declared cooling capacity)	[kW]	4.27	5.63	6.91	8.84	10.06			
EERd (declared EER)	-	4.52	4.54	4.08	4.14	4.17			
Cdc(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90			
Pdc (declared cooling capacity)	[kW]	2.90	3.60	4.58	5.64	6.49			
EERd (declared EER)	-	5.46	5.87	5.95	5.71	5.64			
Cdc(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90			
Pdc (declared cooling capacity)	[kW]	1.33	1.74	2.07	2.75	3.06			
EERd (declared EER)	-	6.91	6.51	6.74	6.76	6.95			
Cdc(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90			



## Product fiche 7

<b>Mini Inverter heat pump space cooling</b>		Outdoor	CRAD3 60 KIAWP	CRAD3 50T KIAWP	CRAD3 55T KIAWP	CRAD3 60T KIAWP
Outdoor unit sound power (*)	Average climate low temperature application	dB	71	69	71	71
	Average climate medium temperature application	dB	71	69	71	71
Space cooling 7°C	Prated (declared cooling capacity) @ 35°C	[kW]	14.2	11.7	13.5	14.2
	Seasonal space cooling efficiency (ηs)	[%]	201.37	201.25	201.81	202.48
	Annual energy consumption	[kWh]	1,670	1,371	1,583	1,661
Space cooling 18°C	Prated (declared cooling capacity) @ 35°C	[kW]	15.3	12.1	14.0	15.3
	Seasonal space cooling efficiency (ηs)	[%]	296.54	311.56	303	298.74
	Annual energy consumption	[kWh]	1,229	923	1,100	1,220
<b>Part load conditions space cooling : low temperature application@7°C</b>						
(A) condition (35°C)	Pdc (declared cooling capacity)	[kW]	14.22	11.67	13.51	14.22
	EERd (declared EER)	-	2.96	3.11	3.01	2.96
	Cdc(degradation coefficient)	-	0.90	0.90	0.90	0.90
(B) condition (30°C)	Pdc (declared cooling capacity)	[kW]	10.62	8.84	10.06	10.62
	EERd (declared EER)	-	4.16	4.14	4.17	4.16
	Cdc(degradation coefficient)	-	0.90	0.90	0.90	0.90
(C) condition (25°C)	Pdc (declared cooling capacity)	[kW]	7.11	5.64	6.49	7.11
	EERd (declared EER)	-	5.72	5.71	5.64	5.72
	Cdc(degradation coefficient)	-	0.90	0.90	0.90	0.90
(D) condition (20°C)	Pdc (declared cooling capacity)	[kW]	3.06	2.75	3.06	3.06
	EERd (declared EER)	-	6.95	6.76	6.95	6.95
	Cdc(degradation coefficient)	-	0.90	0.90	0.90	0.90

## Product fiche 8

<b>Mini Inverter heat pump space cooling</b>		Outdoor	CRAD3 15 KiAWP	CRAD3 25 KiAWP	CRAD3 35 KiAWP	CRAD3 50 KiAWP	CRAD3 55 KiAWP
Part load conditions space cooling : medium temperature application@18°C							
(A) condition (35°C)	Pdc (declared cooling capacity)	[kW]	6.86	8.55	10.24	12.10	14.03
	EERd (declared EER)	-	5.29	4.99	4.42	4.77	4.55
	Cdc(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90
(B) condition (30°C)	Pdc (declared cooling capacity)	[kW]	5.27	6.66	7.81	9.24	10.60
	EERd (declared EER)	-	7.03	6.56	6.34	6.67	6.43
	Cdc(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90
(C) condition (25°C)	Pdc (declared cooling capacity)	[kW]	3.32	4.51	5.16	5.83	7.08
	EERd (declared EER)	-	8.14	9.48	9.50	9.38	8.93
	Cdc(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90
(D) condition (20°C)	Pdc (declared cooling capacity)	[kW]	1.61	1.96	2.51	3.86	3.89
	EERd (declared EER)	-	11.31	11.08	13.78	9.38	9.38
	Cdc(degradation coefficient)	-	0.90	0.90	0.90	0.90	0.90
Air to water unit	Rated airflow (outdoor)	[m <sup>3</sup> /h]	3900	4500	4500	5200	5200
Brine/water to water unit	Rated water/brine flow (outdoor H/E)	-	/	/	/	/	/
	Capacity control	-	Inverter	Inverter	Inverter	Inverter	Inverter
	Poff (Power consumption Off mode)	[kW]	0.013	0.013	0.013	0.013	0.013
	Pto (Power consumption Thermostat off mode)	[kW]	0.005	0.005	0.005	0.005	0.005
	Psb (Power consumption Standby mode)	[kW]	0.013	0.013	0.013	0.013	0.013
	Pck (Power crankcase heater mode)	[kW]	0.000	0.000	0.000	0.000	0.000
	Qelec (Daily electricity consumption)	[kWh]	/	/	/	/	/
	Qfuel (Daily fuel consumption)	[kWh]	/	/	/	/	/
	Other						

## Product fiche 8

<b>Mini Inverter heat pump space cooling</b>		Outdoor	CRAD3 60 KiAWP	CRAD3 50T KiAWP	CRAD3 55T KiAWP	CRAD3 60T KiAWP
Part load conditions space cooling : medium temperature application@18°C						
(A) condition (35°C)	Pdc (declared cooling capacity)	[kW]	15.34	12.10	14.03	15.34
	EERd (declared EER)	-	4.33	4.77	4.55	4.33
	Cdc(degradation coefficient)	-	0.90	0.90	0.90	0.90
(B) condition (30°C)	Pdc (declared cooling capacity)	[kW]	11.44	9.24	10.60	11.44
	EERd (declared EER)	-	6.14	6.67	6.43	6.14
	Cdc(degradation coefficient)	-	0.90	0.90	0.90	0.90
(C) condition (25°C)	Pdc (declared cooling capacity)	[kW]	7.93	5.83	7.08	7.93
	EERd (declared EER)	-	8.95	9.38	8.93	8.95
	Cdc(degradation coefficient)	-	0.90	0.90	0.90	0.90
(D) condition (20°C)	Pdc (declared cooling capacity)	[kW]	3.89	3.86	3.89	3.89
	EERd (declared EER)	-	9.38	9.38	9.38	9.38
	Cdc(degradation coefficient)	-	0.90	0.90	0.90	0.90
Air to water unit	Rated airflow (outdoor)	[m³/h]	5200	5200	5200	5200
Brine/water to water unit	Rated water/brine flow (outdoor H/E)	-	/	/	/	/
	Capacity control	-	Inverter	Inverter	Inverter	Inverter
	Poff (Power consumption Off mode)	[kW]	0.013	0.006	0.006	0.006
	Pto (Power consumption Thermostat off mode)	[kW]	0.005	0.006	0.006	0.006
	Psb (Power consumption Standby mode)	[kW]	0.013	0.006	0.006	0.006
	Pck (Power crankcase heater mode)	[kW]	0.000	0.000	0.000	0.000
	Qelec (Daily electricity consumption)	[kWh]	/	/	/	/
	Qfuel (Daily fuel consumption)	[kWh]	/	/	/	/

Outdoor unit	Ambient Temperature: 35/24 Water temperature: 23/18			Ambient Temperature: 35/24 Water temperature: 12/7			Ambient Temperature: 7/6 Water temperature: 30/35			Ambient Temperature: 2/1 Water temperature: 30/35		
	Capacity kW	Power input kW	EER	Capacity kW	Power input kW	EER	Capacity kW	Power input kW	COP	Capacity kW	Power input kW	COP
CRAD3 15 KiAWP	6.50	1.275	5.10	5.50	1.692	3.25	6.50	1.226	5.30	5.60	1.333	4.20
CRAD3 25 KiAWP	8.30	1.711	4.85	7.40	2.349	3.15	8.40	1.663	5.05	7.10	1.797	3.95
CRAD3 35 KiAWP	10.00	2.326	4.30	9.00	3.103	2.90	10.00	2.128	4.70	8.20	2.158	3.80
CRAD3 50 KiAWP	12.20	2.652	4.60	11.60	3.742	3.10	12.20	2.490	4.90	12.30	3.417	3.60
CRAD3 50T KiAWP	12.20	2.652	4.60	11.60	3.742	3.10	12.20	2.490	4.90	12.30	3.417	3.60
CRAD3 55 KiAWP	13.90	3.159	4.40	13.40	4.573	2.93	14.10	3.000	4.70	13.00	3.714	3.50
CRAD3 55T KiAWP	13.90	3.159	4.40	13.40	4.573	2.93	14.10	3.000	4.70	13.00	3.714	3.50
CRAD3 60 KiAWP	15.40	3.667	4.20	14.00	4.828	2.90	16.00	3.556	4.50	14.50	4.462	3.25
CRAD3 60T KiAWP	15.40	3.667	4.20	14.00	4.828	2.90	16.00	3.556	4.50	14.50	4.462	3.25

Outdoor unit	Ambient Temperature: -7/-8 Water temperature: 30/35			Ambient Temperature: 7/6 Water temperature: 40/45			Ambient Temperature: 2/1 Water temperature: 40/45			Ambient Temperature: -7/-8 Water temperature: 40/45		
	Capacity kW	Power input kW	COP	Capacity kW	Power input kW	COP	Capacity kW	Power input kW	COP	Capacity kW	Power input kW	COP
CRAD3 15 KiAWP	6.20	1.938	3.20	6.60	1.650	4.00	6.50	2.063	3.15	6.10	2.346	2.60
CRAD3 25 KiAWP	7.10	2.254	3.15	8.50	2.237	3.80	7.50	2.459	3.05	6.80	2.720	2.50
CRAD3 35 KiAWP	8.00	2.667	3.00	10.20	2.795	3.65	8.50	2.881	2.95	7.40	3.083	2.40
CRAD3 50 KiAWP	11.60	4.070	2.85	12.50	3.378	3.70	12.00	4.138	2.90	11.50	4.792	2.40
CRAD3 50T KiAWP	11.60	4.070	2.85	12.50	3.378	3.70	12.00	4.138	2.90	11.50	4.792	2.40
CRAD3 55 KiAWP	12.50	4.464	2.80	14.50	4.085	3.55	13.00	4.643	2.80	12.50	5.435	2.30
CRAD3 55T KiAWP	12.50	4.464	2.80	14.50	4.085	3.55	13.00	4.643	2.80	12.50	5.435	2.30
CRAD3 60 KiAWP	13.50	5.000	2.70	16.20	4.696	3.45	14.30	5.296	2.70	13.50	6.000	2.25
CRAD3 60T KiAWP	13.50	5.000	2.70	16.20	4.696	3.45	14.30	5.296	2.70	13.50	6.000	2.25

Outdoor unit	Ambient Temperature: 7/6 Water temperature: 47/55			Ambient Temperature: 2/1 Water temperature: 47/55			Ambient Temperature: -7/-8 Water temperature: 47/55		
	Capacity kW	Power input kW	COP	Capacity kW	Power input kW	COP	Capacity kW	Power input kW	COP
CRAD3 15 KiAWP	6.30	1.969	3.20	6.30	2.250	2.80	5.70	2.651	2.15
CRAD3 25 KiAWP	8.20	2.603	3.15	7.60	2.815	2.70	6.60	3.143	2.10
CRAD3 35 KiAWP	9.40	3.032	3.10	8.40	3.170	2.65	7.20	3.512	2.05
CRAD3 50 KiAWP	12.00	4.000	3.00	12.00	5.106	2.35	10.80	5.143	2.10
CRAD3 50T KiAWP	12.00	4.000	3.00	12.00	5.106	2.35	10.80	5.143	2.10
CRAD3 55 KiAWP	14.00	4.746	2.95	13.00	5.603	2.32	11.70	5.625	2.08
CRAD3 55T KiAWP	14.00	4.746	2.95	13.00	5.603	2.32	11.70	5.625	2.08
CRAD3 60 KiAWP	16.00	5.614	2.85	13.50	5.870	2.30	12.80	6.244	2.05
CRAD3 60T KiAWP	16.00	5.614	2.85	13.50	5.870	2.30	12.80	6.244	2.05

# dzitsu

**EUROFRED**  
*being efficient*

Eurofred S.A.  
Marqués de Sentmenat 97  
08029 Barcelona  
[www.eurofred.es](http://www.eurofred.es)