ABS | Upright Cabinets

REFRIGERATED UPRIGHT ► GLASS DOOR ► INOX



GENERAL FEATURES

400 Lt. Refrigerated upright (GLASS DOOR)	•
S/S external cabinet, thermoformed internally	•
Roll-bond evaporator system with fan assisted cooling	•
Automatic compressor cycle defrost	•
Foaming Agent Cyclopentane (70mm per side)	•
Digital Thermostat and internal LED light	•
High temperature alarm	•
Removable Gasket	•
Door: Self closing and reversible door fitted as standard	•
Lock and main switch fitted as standard	•
Adjustable shelves: 4 Pcs + 1 Pcs Bottom	•
N.2 Adjustable feet + N.2 Rollers at the back	•
Stainless steel external handle	•
Energy efficiency class: D	•

TECHNICAL SPECIFICATIONS

Capacity	400 L
Temperature	+2°C ~ +8°C
Consumption	1.609 kWh/24h
Rated Power	120 W
Noise level	53 dB(A)
Net Weight	96.5 Kg
Gross Weight	107 Kg
External Dimensions (WxDxH mm)	600x708x1875
Internal Dimensions (WxDxH mm)	460x467x1643
Packaging dimensions (WxDxH mm)	660x705x2060
Loading quantities 20'/40'/40'HQ	24/54/54

CERTIFICATION



































Air circulating fan assistance





Shelf with small distance between the line and bottom shelf fittes as standard



External cylindric handle in stainless steel (Steel color for X Version)

PRODUCT DIMENSIONS

